

FRIGOBOAT CONDENSING UNITS DC: FRIGOMATIC / MOTOCONDENSANTI FRIGOBOAT IN CC: FRIGOMATIC

Product details and technical specifications

Litri Max per frigo	Nome prodotto	Codice prodotto	Tipo di espansione	Raffreddamento	RPM	Capacità (Btu/h)	Consumo (A)	Consumo (W)	peso (kg)	Peso spedizione(kg)	Dimensione (LxDxH*)	Refrigerante
Max Liters per fridge	Product Name	Product Code	Expansion	Cooling by	RPM	Capacity (Btu/h)	Consumption (A)	Consumption (W)	Weight (kg)	Shipping Weight (kg)	Size (LxDxH*)	Refrigerant
100	MADRID 35 F	E51380	capillar	Air	2000	225	3,40		5,80	6,60	231x128x288	r134a
100	PARIS 35F	E51135	capillar	Air	2000	225	3,40	36	6,30	6,90	230x300x168	r134a
100	ROMA 35 F	E51275	capillar	Air	2000	225	3,40	41	6,20	7,00	345x210x165	r134a
100	FM100	E52270	capillar	Air	2000	225	3,40	36	6,30	6,90	200x224x169	r134a
200	ELBA 35F	E51435	capillar	Air	2000	247	3,20	37	7,4	8	310x238xXXX	r134a
					2500	280	4,10	49				
					3000	325	4,70	57				
					3500	373	5,50	66				
200	CAPRI 35F	E51430	capillar	Air	2000	247	3,20	37	8,5	9,5	266x239x170	r134a
					2500	280	4,10	49				
					3000	325	4,70	57				
					3500	373	5,50	66				
200	FM 200	E52375	capillar	Air	2000	247	3,20	37	7,4	8	300x180x164	r134a
					2500	280	4,10	49				
					3000	325	4,70	57				
					3500	373	5,50	66				
340	AH 35 F	E50035X	capillar	Air	2000	274	3,20	37	6,3	7,1	332x220x168	r134a
					2500	311	4,00	48				
					3000	396	4,60	56				
					3500	454	5,40	65				
340	K 35 F	E50345X	capillar	keel	2000	326	3,00	31	5,8	6,6	260x145x170	r134a
					2500	406	3,40	40				
					3000	471	3,90	47				
					3500	540	4,60	56				
340	W 35 F	E50045X	capillar	water	2000	326	4,00	45	5,8	6,6	260x160x180	r134a
					2500	406	4,70	56				
					3000	471	5,70	66				
					3500	540	6,80	81				

Litri Max per frigo	Nome prodotto	Codice prodotto	Tipo di espansione	Raffreddamento	RPM	Capacità (Btu/h)	Consumo (A)	Consumo (W)	peso (kg)	Peso spedizione(kg)	Dimensione (LxDxH*)	Refrigerante
Max Liters per fridge	Product Name	Product Code	Expansion	Cooling by	RPM	Capacity (Btu/h)	Consumption (A)	Consumption (W)	Weight (kg)	Shipping Weight (kg)	Size (LxDxH*)	Refrigerant
340	AV 35 F	E50025X	capillar	Air	2000	274	3,20	37	6,3	7,1	218x165x297	r134a
					2500	311	4,00	48				
					3000	396	4,60	56				
					3500	454	5,40	65				
340	CAPRI 50 F	E52120	capillar	Air	2000	326	4,30	49	8,5	-	283x255x170	r134a
					2500	410	5,40	64				
					3000	490	6,50	75				
					3500	565	7,50	89				
340	AHL 35 F	E52085	capillar	Air	2000	274	3,20	37	6,3	-	-	r134a
					2500	311	4,00	48				
					3000	396	4,60	56				
					3500	454	5,40	65				
380	K 50	E51975	capillar	keel	2000	369	4,00	45	5,8	6,6	260x145x170	r134a
					2500	472	4,70	56				
					3000	560	5,70	66				
					3500	650	6,80	81				
380	W 50	E51970	capillar	water	2000	369	4,00	45	5,8	-	260x232x180	r134a
					2500	472	4,70	56				
					3000	560	5,70	66				
					3500	650	6,80	81				
500	W 80	EW80	capillar	water	2000	369	4,00	45	5,8	-	-	r134a
					2500	472	4,70	56				
					3000	560	5,70	66				
					3500	650	6,80	81				
500	K 80	EK80	capillar	keel	2000	369	4,00	45	5,8	-	-	r134a
					2500	472	4,70	56				
					3000	560	5,70	66				
					3500	650	6,80	81				